

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** Some pages contains small letters

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.

THIS PAGE BLANK (USPTO)

(19) World Intellectual Property Organization
International Bureau




(43) International Publication Date
7 March 2002 (07.03.2002)

PCT

(10) International Publication Number
WO 02/19269 A2

- (51) International Patent Classification⁷: **G06T 1/00** (81) Designated States (*national*): AE, BG, BR, CA, CN, CZ, DK, DZ, HU, IL, IN, IS, JP, KP, KR, MX, PL, RO, RU, UA.
- (21) International Application Number: PCT/CA01/01146
- (22) International Filing Date: 14 August 2001 (14.08.2001) (84) Designated States (*regional*): European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR).
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 09/648,424 28 August 2000 (28.08.2000) US
- (71) Applicant and (72) Inventor: PEREIRA, Shelby [CA/CA]; Canada, 5773 Smart Avenue, Montreal, Québec H4W-2M8 (CA).
- Published:
— without international search report and to be republished upon receipt of that report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.



WO 02/19269 A2

(54) Title: A METHOD FOR ENCODING AND DECODING IMAGE DEPENDENT WATERMARKS

(57) Abstract: A method for generating signal dependent wa-termarks is described. The method is based on a novel coding technique based on the use of absolute values which renders the watermark dependent on the image. Various embodiments are described in which 1 bit or a group of several bits are encoded by using a function containing one or more levels of absolute value. The de-coding is straightforward and consists of calculating the function used at embedding and comparing it against a threshold to determine if a 1 or 0 was embedded. The method is described for the particular case of images and individual video frames, but is easily applicable to any digital signal including audio signals.

BEST AVAILABLE COPY

A method for encoding and decoding image dependent watermarks

Technical Field

The present invention relates to methods of generating and decoding watermarks in images according to the preamble of the independent claims.

Background Art

The present invention relates to methods of generating and decoding image dependent watermarks in a novel way which simultaneously addresses one or more critical problems not solved by current methods.

The idea of using a robust digital watermark to detect and trace copyright violations has stimulated significant interest among artists and publishers in recent years. Podilchuk (Podilchuk & Zeng 1998) gives three important requirements for an effective watermarking scheme: transparency, robustness and capacity. Transparency refers to the fact that we would like the watermark to be invisible. The watermark should also be robust against a variety of possible image processing attacks by pirates. These include robustness against compression such as JPEG, scaling and aspect ratio changes, rotation, cropping, row and column removal, addition of noise, filtering, cryptographic and statistical attacks, as well as insertion of other watermarks (Petitcolas & Anderson 1998) and the watermark copy attack proposed by Kutter (Kutter, Voloshynovskiy & Herrigel 2000) in which a watermark is estimated from one image and added to another one.

The third requirement is that the watermark be able to carry a certain amount of information i.e. capacity. In order to attach a unique identifier to each buyer of an image, a typical watermark should be able to

carry at least 60-100 bits of information. However few publications deal with 60 or more bits.

Watermarking methods can be divided into two broad categories: spatial domain methods such as (Bender, Gruhl & Morimoto 1996, Pitas 1996) and transform domain methods which have for the most part focused on DCT (Podilchuk & Zeng 1998, Barni et al. 1998), DFT (Pereira & Pun 1999, Barni, Bartolini, Rosa & Piva 1999) and most recently wavelet domain methods (Podilchuk & Zeng 1998, Barni, Bartolini, Cappellini, Lippi & Piva 1999, Zhu, Xiong & Zhang 1999). Transform domain methods have several advantages over spatial domain methods. Firstly, it has been observed that in order for watermarks to be robust, they must be inserted into the perceptually significant parts of an image. For images these are the lower frequencies which can be marked directly if a transform domain approach is adopted (Cox, Killian, Leighton & Shamoon 1996). Secondly, since compression algorithms operate in the frequency domain (for example DCT for JPEG and wavelet for EZW) it is possible to optimize methods against compression algorithms. Thirdly, certain transforms are intrinsically robust to certain transformations. For example, the DFT domain has been successfully adopted in algorithms which attempt to recover watermarks from images which have undergone affine transformations (Pereira & Pun 1999).

While transform domain watermarking clearly offers benefits, the problem is more challenging since it is more difficult to generate watermarks which are adapted to the human visual system (HVS). One possibility which has recently appeared is the attempt at specifying the mask in the transform domain (Podilchuk & Zeng 1998). Podilchuk and Zeng have accurately modeled the masking in both the wavelet and discrete cosine transform (DCT) domains where it is shown how to obtain the allowable distortion at a given coefficient as a function of all other coefficients.

The existing technologies exhibit at least one of the following problems:

1. Less than 60 bits are encoded.
2. sub-optimal spatial domain modulation is applied to reduce visibility.
3. The watermark is not image dependent and in particular does not resist against the watermark copy attack which estimates the watermark from one image and adds it to another.
4. Uses an additive watermark which is easily copied, or attacked by denoising and perceptual remodulation as proposed by Voloshynovskiy (Voloshynovskiy, Herrigel, Baumgärtner, Pereira & Pun 2000).
5. At embedding the image is treated as noise.

It is the object of the present invention to provide a method of embedding a watermark which simultaneously is capable of dealing with the 5 stated problems.

In one aspect, the invention consists of formulating the problem as a constrained optimized problem, in which the optimization takes place over the watermarking domain with constraints on visibility posed in (possibly) another domain. Furthermore, the image is not treated as noise, but as a sequence of known values which leads to a much better performance.

In another aspect, in order to render the watermark image dependent, a coding scheme is described in which coding 1 or more bits depends explicitly on the values of one or more transform or spatial domain coefficients. Since these coefficients vary from image to image, copying of the watermark will not result in a successful detection. In fact this coding scheme renders the watermark non-additive which is essential in resisting the copy attack. The non-additive and highly adaptive nature also makes the watermark extremely robust.

In yet another aspect, it is shown how to incorporate the knowledge of JPEG quantization tables or

any other quantization tables such as MPEG, LZW or others in order to render the watermark more resistant to compression.

In another aspect, we indicate how to apply the algorithm to video watermarking and music watermarking.

Disclosure of the Invention

It is the object of the present invention to provide a method of the type mentioned above that is capable of dealing with at least some, preferably all of these problems.

According to the present invention, the problem is solved by the method of the independent claims.

Preferred embodiments are described in the dependent claims.

The present method is suited for watermarking still images or video data or music signals. While the primary goal of watermarking is copyright protection, the method is also suited for other applications such as steganography where we are interested in embedding information in a medium.

Modes for Carrying Out the Invention

Formulation of preferred embodiments:

We formulate the embedding process as a constrained optimization problem. We assume that we are given an image to be watermarked denoted I . If it is an RGB image we work with the luminance component though the same methodology can be applied to other color spaces where one or more of the color components are being watermarked. We are also given a masking function $V(I)$ which returns a matrix of the same size of I containing the values $\Delta_{i,j}$ corresponding to the amount by which co-

efficient (i, j) can be changed without being noticed. Δ can be computed in either a transform domain or the spatial domain by noise visibility functions NVF as proposed by Voloshynovskiy (Voloshynovskiy, Herrigel, Baumgaertner & Pun 1999) or other visual models such as those proposed by Osberger (Osberger, Bergmann & Maeder 1998) or Podilchuk (Podilchuk & Zeng 1998).

In the general case, the function V can be a complex function of texture, luminance, contrast, frequency and patterns. We wish to embed a binary message m where M is the number of bits in the message. In general, the binary message may first be augmented by a checksum and/or coded using error correction codes such as BCH or turbo codes to produce a message $m_C = (m_1, m_2, \dots, m_{N_t})$ of total length N_t . Without loss of generality we assume the image I is of size 128×128 corresponding to a very small image. For larger images the same procedure is adopted for each 128×128 large block.

To embed the message, we first divide the image into 8×8 blocks and calculate the DCT of each block. In each 8×8 DCT block we embed N_b bits from m_C . For each bit m_i we select 2 coefficients c_1 and c_2 based on a key, in which we will embed the information bit. For better performance each coefficient in a block should only be used once so that in general it is understood that for a different m_i , c_1 and c_2 are different. We recall that in order to ensure the watermark remains invisible, we must insist that c_1 and c_2 do not change more than the allowed $\Delta_{i,j}$ for the coefficient as determined by the function $V(I)$.

From this basic setup, several strategies can be adopted to embed the message. In one embodiment, we encode a 1 by maximizing $|c_1 - c_2|$ while to encode a 0 we minimize $|c_1 - c_2|$. The key advantage arises from the use of the absolute value. The main idea is that to maximize $|c_1 - c_2|$ we will increase c_1 and decrease c_2 if $c_1 > c_2$ otherwise we will increase c_2 and decrease c_1 . in order to

minimize $|c_1 - c_2|$ we will move c_1 and c_2 so that they are as close as possible to being equal. It is also possible to move them both towards 0 although this will typically cost more energy. Whether we maximize or minimize we note that the embedding depends on the original values c_1 and c_2 which vary from image to image. This is the key to rendering the scheme image dependent and thereby resistant to the copy attack.

As is obvious to a person skilled in the art the maximization and minimization may be inverted at embedding. The compensation at decoding is straightforward. Once the coefficients have been modified in the DCT domain, the inverse DCT block by block is computed to obtain the watermarked image in the spatial domain.

In order to decode the watermark we simply calculate $|c_1 - c_2|$ associated with each bit and then compare it to a threshold T . If it is larger than T we assign 1 to the bit otherwise we assign 0. The error correction codes are then decoded and the checksum tested if necessary. In a superior embodiment, rather than assigning 1 and 0 after comparison to a threshold (known as hard decoding) we can retain the values $|c_1 - c_2| - T$ and use them directly in the soft decoding of error correction codes which may yield a gain of more than 3dB in some cases. Typically the threshold T is calculated empirically by testing the algorithm and choosing a T which yields the best performance.

In the above simple embodiments we have used the function $|c_1 - c_2|$ for embedding. In other embodiments functions of the form $|f(c_1, c_2, c_3, c_4, \dots)|$ may be interesting. In particular, rather than using just a difference of two coefficients, we may calculate a linear combination of several coefficients prior to taking the absolute value. Another possibility is to multiply coefficients. Yet another embodiment consists of using several levels of absolute values. In other words, we would calculate

$||c_1| - |c_2||$ or the absolute value of a linear combination of absolute values in general. In all cases the principle used for decoding remains the same. That is we calculate the function used at embedding and then use soft or hard decoding of error correction codes. Preferred embodiments would use turbo codes which approach optimal performance in Gaussian channels.

In the above embodiments we have chosen to encode each bit separately by modulating a set of coefficients as determined by a function. In a fundamentally different embodiment we can encode several bits by the maximization and minimizations of functions of the form $|f(c_1, c_2, c_3, c_4...)|$.

Table 1: Encoding of multiple bits

Bits	associated function
00	$ c_1 - c_2 $
01	$ c_3 - c_4 $
10	$ c_5 - c_6 $
11	$ c_7 - c_8 $

As an example of the encoding scheme, table 1 associates pairs of bits with a given function which in this embodiment is just the absolute value of the difference between 2 coefficients. If we would like to encode 00 we would maximize $|c_1 - c_2|$ and minimize $|c_3 - c_4|$, $|c_5 - c_6|$ and $|c_7 - c_8|$. Clearly in other embodiments we may use more general functions of the form $|f(c_1, c_2, c_3, c_4...)|$ as described previously. The decoding for this embedding strategy is straightforward. We must simply calculate the associated functions and choose the bit pair which corresponds to the maximum. We also note that more than two bits can be used however the number of functions and therefore the encoding and decoding complexity required goes up exponentially. In other embodiments Reed-Solomon codes or low density parity check codes (LDPC) are used

when bits are grouped together at embedding since these tend to perform better in these situations.

In what has been described, the DCT domain has been used, however any other domain may also be used for the embedding. In the case of spatial domain embedding, typically the local mean would first be removed. Although this is not necessary, if we do this, we obtain coefficients whose expected value is 0. This is the case for most transform domains since the mean is represented by one coefficient in a given block. In the case of the wavelet domain, the coefficients representing the local means, are contained in the lowest subband. Using zero mean coefficients considerably simplifies the embedding since the mean must no longer be accounted for at decoding.

We note that it is now well known that a synchronization pattern can be added to the watermark. At decoding the synchronizing pattern is searched for. If the image has undergone geometrical transformations, these are compensated for and then the watermark is decoded. An example of a synchronization pattern commonly used is a set of peaks in the Fourier transform domain as done in (Pereira & Pun 1999). Consequently in all the embodiments, it is to be understood that synchronization patterns can be done with little or no effect on the watermark itself since the energy used in the pattern is typically much less than the energy of the watermark.

While there are shown and described presently preferred embodiments of the invention, it is to be distinctly understood that the invention is not limited thereto but may be otherwise variously embodied and practiced within the scope of the following claims.

References:

- Barni, M., Bartolini, F., Cappellini, V., Lippi, A. & Piva, A. (1999), A DWT-based technique for spatio-frequency masking of digital signatures, in P. W. Wong & E. J. Delp, eds, 'Security and Watermarking of Multimedia Contents', Vol. 3657, The Society for Imaging Science and Technology (IS&T) and the International Society for Optical Engineering (SPIE), SPIE, San Jose, California, U.S.A., pp. 31-39.
*<http://lci.die.unifi.it/Publications/swmc99-04.ps.gz>
- Barni, M., Bartolini, F., Cappellini, V., Piva, A. & Rigacci, F. (1998), A M.A.P. identification criterion for DCT-based watermarking, in 'EUSIPCO'98', Rhodes, Greece.
- Barni, M., Bartolini, F., Rosa, A. D. & Piva, A. (1999), Capacity of the watermark-channel: How many bits can be hidden within a digital image ?, in 'SPIE: Security and Watermarking of Multimedia Contents', Vol. 3657, San Jose, California, pp. 437-448.
- Bender, W., Gruhl, D. & Morimoto, N. (1996), 'Method and apparatus for data hiding in images', *U.S. Patent # 5689587*.
- Cox, I. J., Miller, M. L. & McKellips, A. L. (1999), 'Watermarking as communications with side information', *Proceedings of the IEEE* 87(7), 1127-1141.
- Cox, I., Killian, J., Leighton, T. & Shamoon, T. (1996), Secure spread spectrum watermarking for images, audio and video., in 'Proceedings of the IEEE Int. Conf. on Image Processing ICIP-96', Lausanne, Switzerland, pp. 243-246.
- Kutter, M., Voloshynovskiy, S. & Herrigel, A. (2000), Watermark copy attack, in P. Wah Wong & E. J. Delp, eds, 'IS&T/SPIE's 12th Annual Symposium, Electronic Imaging 2000: Security and Watermarking of Multimedia Content II', Vol. 3971 of *SPIE Proceedings*, San Jose, California USA.
- Osberger, W., Bergmann, N. & Maeder, A. J. (1998), An automatic image quality assessment technique incorporating higher level perceptual factors, in 'IEEE ICIP-98', Chicago, USA.
- Pereira, S. & Pun, T. (1999), Fast robust template matching for affine resistant watermarks, in '3rd International Information Hiding Workshop', Dresden, Germany.
- Pereira, S. & Pun, T. (2000), A framework for optimal adaptive dct watermarks using linear programming, in 'Tenth European Signal Processing Conference (EUSIPCO'2000)', Tampere, Finland.
- Petitcolas, F. A. P. & Anderson, R. J. (1998), Attacks on copyright marking systems, in '2nd International Information Hiding Workshop', Portland, Oregon, USA, pp. 219-239.

- Pitas, I. (1996), A method for signature casting on digital images, in 'Proceedings of the IEEE Int. Conf. on Image Processing ICIP-96', Lausanne, Switzerland, pp. 215-218.
- Podilchuk, C. I. & Zeng, W. (1998), 'Image-adaptive watermarking using visual models', *IEEE Journal on Selected Areas in Communications* 16(4), 525-539.
- Swanson, M. D., Zhu, B. & Tewfik, A. (1996), Robust data hiding for images, in '7th IEEE Digital Signal Processing Workshop', Loen, Norway, pp. 37-40. G:WM1-A23.
- Swanson, M. D., Zhu, B. & Tewfik, A. H. (1998), 'Multiresolution scene-based video watermarking using perceptual models', *IEEE Journal on Selected Areas in Communications* 16(4), 540-550.
- Vetterli, M. & Kovacević, J. (1995), *Wavelets and Subband Coding*, Prentice Hall.
- Voloshynovskiy, S., Herrigel, A., Baumgaertner, N. & Pun, T. (1999), A stochastic approach to content adaptive digital image watermarking, in 'Third International Workshop on Information Hiding', Dresden, Germany.
- Voloshynovskiy, S., Herrigel, A., Baumgärtner, N., Pereira, S. & Pun, T. (2000), A generalized watermark attack based on stochastic watermark estimation and perceptual remodulation, in P. Wah Wong & E. J. Delp, eds, 'IS&T/SPIE's 12th Annual Symposium, Electronic Imaging 2000: Security and Watermarking of Multimedia Content II', Vol. 3971 of *SPIE Proceedings*, San Jose, California USA. (Paper EI 3971-34).
- Voyatzis, G. & Pitas, I. (1999), 'The use of watermarks in the protection of digital multimedia products', *Proceedings of the IEEE* 87(7).
- Zhu, W., Xiong, Z. & Zhang, Y. Q. (1999), 'Multiresolution watermarking for images and video', *IEEE Transactions on Circuits and Systems for Video Technology* 9(4), 545-550.

Claims

1. A method for embedding a watermark in a still or non-still image or music signal or other digital signal I comprising the steps of:

selecting coefficients c_i from a set $c = \{c_1, \dots, c_N\}$ of coefficients, wherein said set of coefficients corresponds to said signal I or a transform thereof, and wherein said coefficients c_i are selected to be used for encoding a message m_c or a message derived from m_c by use of error correction codes, and modifying each of said selected coefficients c_i to encode one or more bits of said message by minimizing or maximizing functions of the form $|f(c_1, c_2, c_3, c_4, \dots)|$.

2. The method of claim 1 wherein said function f is of the form $|k_1*c_1+k_2*c_2+k_3*c_3+\dots+k_n*c_n|$ where the values k are constants and at least 2 coefficients k_1 and k_2 are non zero.

3. The method of claim 2 where k_1 is 1 and k_2 is -1.

4. The method of claim 1 where the function is $|k_1|c_1|-k_2|c_2||$ where the values k are constants.

5. The method of one of the preceding claims applied to the spatial domain, where the local mean has first been removed.

6. The method of one of the preceding claims wherein said coefficients c_i are constrained by values $\Delta_{i,j}$ as determined by a masking function of the data set $V(I)$.

7. The method of claim 6 where bits are first grouped together and each possible bit group is assigned a function and the function corresponding to the bit group to be embedded is maximized while the others are minimized.

8. The method of claim 7 where Reed-Solomon codes or LDPC codes are used to encode the original message prior to embedding.

9. A method for decoding the watermark generated by the method of one of the preceding claims (except claims 7 and 8) comprising the step of calculating the function $|f(c_1, c_2, c_3, c_4...)|$ and comparing it to a threshold value T , and assigning a value of 1 if greater than T and 0 otherwise and then decoding error correction codes if necessary.

10. The method of claim 9 where soft decoding is used based on the difference $|f(c_1, c_2, c_3, c_4...)| - T$.

11. A method for decoding a watermark generated by the method of claims 7 or 8 consisting of calculating all the functions used at embedding and choosing the bit sequence associated with the function yielding the maximum value, and decoding the error correction codes if necessary after the entire bit sequence has been retrieved.

12. A method for watermarking video data comprising a plurality of consecutive video frames, wherein the method of one of the claims 1-11 is applied to at least some of said video frames.

13. A method for watermarking a 1D music signal wherein the method of one of the claims 1-11 is applied to at least some of said music signal.

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
7 March 2002 (07.03.2002)

PCT

(10) International Publication Number
WO 02/19269 A3

- (51) International Patent Classification⁷: **G06T 1/00** (84) Designated States (*regional*): European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR).
- (21) International Application Number: **PCT/CA01/01146**
- (22) International Filing Date: **14 August 2001 (14.08.2001)** Published:
— with international search report
— before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments
- (25) Filing Language: **English**
- (26) Publication Language: **English**
- (30) Priority Data: **09/648,424** **28 August 2000 (28.08.2000)** **US** (88) Date of publication of the international search report: **2 May 2002**
- (71) Applicant and (72) Inventor: **PEREIRA, Shelby** [CA/CA]; Canada, 5773 Smart Avenue, Montreal, Québec H4W-2M8 (CA).
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(81) Designated States (*national*): AE, BG, BR, CA, CN, CZ, DK, DZ, HU, IL, IN, IS, JP, KP, KR, MX, PL, RO, RU, UA.



WO 02/19269 A3

(54) Title: A METHOD FOR ENCODING AND DECODING IMAGE DEPENDENT WATERMARKS

(57) Abstract: A method for generating signal dependent wa-termarks is described. The method is based on a novel coding technique based on the use of absolute values which renders the watermark dependent on the image. Various embodiments are described in which 1 bit or a group of several bits are encoded by using a function containing one or more levels of absolute value. The de-coding is straightforward and consists of calculating the function used at embedding and comparing it against a threshold to determine if a 1 or 0 was embedded. The method is described for the particular case of images and individual video frames, but is easily applicable to any digital signal including audio signals.

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 G06T1/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 G06T

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, INSPEC, IBM-TDB, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	<p>MUKHERJEE D ET AL: "A SOURCE AND CHANNEL CODING APPROACH TO DATA HIDING WITH APPLICATION TO HIDING SPEECH IN VIDEO" PROCEEDINGS OF THE 1998 INTERNATIONAL CONFERENCE ON IMAGE PROCESSING. ICIP '98. CHICAGO, IL, OCT. 4 - 7, 1998, INTERNATIONAL CONFERENCE ON IMAGE PROCESSING, LOS ALAMITOS, CA: IEEE COMPUTER SOC, US, vol. 1 CONF. 5, October 1998 (1998-10), pages 348-352, XP000668952 ISBN: 0-8186-8822-X page 348, right-hand column, line 28 -page 349, right-hand column, line 7</p> <p style="text-align: center;">--- -/--</p>	1-6,11

☒ Further documents are listed in the continuation of box C.☐ Patent family members are listed in annex.

* Special categories of cited documents:

A document defining the general state of the art which is not considered to be of particular relevance

E earlier document but published on or after the international filing date

L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

O document referring to an oral disclosure, use, exhibition or other means

P document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

Z document member of the same patent family

Date of the actual completion of the international search

13 March 2002

Date of mailing of the international search report

20/03/2002

Name and mailing address of the ISA

European Patent Office, P.B. 5618 Patentlaan 2
NL - 2280 HV Rijswijk
Tel: (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Burgaud, C

INTERNATIONAL SEARCH REPORT

International Application No

PCT/CA 01/01146

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	<p>SERVETTO S D ET AL: "CAPACITY ISSUES IN DIGITAL IMAGE WATERMARKING" PROCEEDINGS OF THE 1998 INTERNATIONAL CONFERENCE ON IMAGE PROCESSING. ICIP '98. CHICAGO, IL, OCT. 4 - 7, 1998, INTERNATIONAL CONFERENCE ON IMAGE PROCESSING, LOS ALAMITOS, CA: IEEE COMPUTER SOC, US, vol. 1 CONF. 5, 4 October 1998 (1998-10-04), pages 445-449, XP000953823 ISBN: 0-8186-8822-X page 446, right-hand column, line 55 -page 447, left-hand column, line 34 -----</p>	1-6,11